



# TTS GREEN TROUGH - COMPLETE CABLE TROUGHING SYSTEMS

Concrete	TTS SYSTEM	WEIGHT SAVING OVER STANDARD CONCRETE*		STRAIGHTS	CURVES	JUNCTIONS	GRADIENTS	EXTRA CAPACITY OVER CONCRETE	TTS SYSTEM Internal Capacity	Concrete Internal Capacity
		OVER STANDARD CONCRETE*	OVER LIGHT CONCRETE*							
C / 1 / 6	<b>70 Series</b>	<b>88 %</b>	<b>82 %</b>	✓	✓	✓	✓	<b>-25 %</b>	5,600 mm <sup>2</sup>	7,500 mm <sup>2</sup>
C / 1 / 6	<b>120 Series</b>	<b>83 %</b>	<b>74 %</b>	✓	✓	✓	✓	<b>60 %</b>	12,000 mm <sup>2</sup>	7,500 mm <sup>2</sup>
C / 1 / 7	<b>150 Series</b>	<b>83 %</b>	<b>74 %</b>	✓	✓	✓	✓	<b>35 %</b>	20,250 mm <sup>2</sup>	14,950 mm <sup>2</sup>
C / 1 / 8	<b>200 Series</b>	<b>79 %</b>	<b>67 %</b>	✓	✓	✓	✓	<b>33 %</b>	37,000 mm <sup>2</sup>	27,750 mm <sup>2</sup>
C / 1 / 9	<b>200 Series</b>	<b>76 %</b>	<b>64 %</b>	✓	✓	✓	✓	<b>69 %</b>	37,000 mm <sup>2</sup>	21,850 mm <sup>2</sup>
C / 1 / 10	<b>250 Series</b>	<b>73 %</b>	<b>58 %</b>	✓	✓	✓	✓	<b>52 %</b>	43,750 mm <sup>2</sup>	28,750 mm <sup>2</sup>
C / 1 / 29	<b>300 Series</b>	<b>80 %</b>	<b>70 %</b>	✓	✓	✓	✓	<b>30 %</b>	52,500 mm <sup>2</sup>	40,250 mm <sup>2</sup>
C / 1 / 43	<b>430 Series</b>	<b>73 %</b>	<b>59 %</b>	✓	✓	✓	✓	<b>15 %</b>	114,750 mm <sup>2</sup>	99,750 mm <sup>2</sup>

\* Per linear metre

\* Per linear metre

SYSTEM INCLUDES · STRAIGHTS · CURVES · JUNCTIONS · GRADIENTS

For more information about TTS Green Trough, or the HSE MAC Tool Assessment of concrete and polymer trough products, call our technical team on +44 (0)1302 343 633, or email [info@ttshighway.co.uk](mailto:info@ttshighway.co.uk). Alternatively visit our website [www.ttshighway.co.uk](http://www.ttshighway.co.uk)